



IQTouch TE1100 v3.0



Data Sheet

- **The advanced Android 11.0**
Latest Android version on IFP, faster processing speed and more stable performance.
- **4K UHD display with zero bonding**
Support for all-channel 4K UI display with high brightness and high contrast.
- **USB-C connectivity**
Instantly connect your own device for hassle-free presentations via a single-cable solution for touch, audio, video, and power.
- **Annotation on any source**
Switch freely among different input sources while making direct annotations.
- **BYOD**
Easy to share the ideas and collaborate with the rest of the team by wireless screen sharing.



IQTouch TE1100 v3.0 Specifications

Display

Model	LE065MD	LE075MD	LE086MD
Diagonal Size	65"	75"	86"
Max brightness	400cd/m2		
Contrast Ratio	5000:1		
Panel Type	TFT		
Backlight	Direct LED (DLED)		
Resolution	4K UHD (3840*2160)		
Aspect Ratio	16:9		
Response Rate	6m/s		
Refreshing Frequency	60Hz		
Viewing Angle	178° (H), 178° (V)		
Backlight Life Time	50,000 hrs		
Display Colors	10bit(1.07B)		
Glass	4mm Anti-Glare Tempered Glass with Zero Bonding (MOHS 7)		

Interactivity

Touch Technology	Infrared
Touch Point	20-point touch/writing
Touch Resolution	32768 x 32768
Response Rate	<4ms(single touch) <6ms(max touch inputs)
Touch Accuracy	≤1mm
Recognition	Finger or passive stylus
Writing Height	2mm
Minimum Touch Object	2mm
Supported O.S.	HID Support & Win10/Win8/Win7/Mac OS /Android/Chrome OS/Linux

Power

	65"	75"	86"
Voltage	100-240V, 50-60 Hz	100-240V, 50-60 Hz	100-240V, 50-60 Hz
Maximum Power	≤250W	≤350W	≤450W
Standby Power	≤0.5W	≤0.5W	≤0.5W

Physical Specifications

	65"	75"	86"
Net Weight	40Kg ± 1 Kg	56Kg ± 1 Kg	66Kg ± 1 Kg
Gross Weight	46Kg ± 1 Kg	70Kg ± 1Kg	81Kg ± 1Kg
Product Size (mm) (W*D*H)	1490* 887*89	1712* 1013*89	1959* 1152*89
Packing Size (mm) (W*D*H)	1576* 980*200	1800* 1125*200	2044* 1262*200
VESA Hole Position (mm)	4-M8 screw hole 500*400	4-M8 screw hole 600*400	4-M8 screw hole 800*400

Environmental

Working Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Working Humidity	20% ~ 80% RH Non-Condensing
Storage Humidity	20% ~ 90% RH Non-Condensing



Front Buttons

8 Buttons	Home,Back,Source,Vol-,Vol+,Setting,Power
-----------	--

Connectivity

Front	USB3.0 (Android&PC)	3
	HDMI IN 2.0	1
	Touch-USB	1
	Type C	1
Input	RJ45	1
	HDMI 2.0	2
	VGA	1
	Audio	1
	USB 2.0 (Android)	1
	USB 3.0 (Android)	1
	AV	1
	RS232	1
	YPBPR	1
	Touch-USB	1
Output	HDMI 2.0	1
	COAX SPDIF	1
	AV	1
	EARPHONE	1
Speakers	15W*2	
Light Sensor	YES	
Temperature Monitor	YES	
WiFi & Hotspot	802.11 a/b/g/n/ac embedded (2.4G/5G Dual Module)	
Bluetooth	5.0	

Language

OSD	English,Simplified Chinese,etc.
-----	---------------------------------

Android

CPU Framework	Quad-core A55
CPU Processor Speed	2.0GHz
GPU	Mail G52MP2
RAM	4GB DDR4
ROM	32GB EMMC
OS Version	Android 11.0
IQ OS	YES

OPS-C

Chipset	Intel,12th gen
CPU	Intel®Core i3
Memory	8GB DDR4
SSD	128GB
NETWORK	1×RTL811110/100/1000M (RJ45) 1×WIFI(NGFF) (support802.11ac/a/b/g/n;BT4.2)

OPS-C Interfaces

USB3.2 GEN1	1
USB3.0	4
USB2.0	1
USB type-c	1
HDMI OUT	1
DP	1
LINE-OUT	1
MIC-IN	1

